



FXAQ15-32P



BRC1E52A/B BRC7E618

- > Ideal solution for shops, restaurants or offices with no or narrow false ceilings
- > Low energy consumption thanks to DC fan motor
- > Can be installed in both new and existing buildings
- > Flat, stylish front panel blends easily within any interior décor and is more easy to clean
- > 15 class unit especially developed for small or well-insulated rooms, such as hotel bedrooms, small offices, etc.
- > 5 different discharge angles can be programmed via the remote control
- > Maintenance operations can be performed from the front of the unit



INDOOR UNIT			FXAQ15P	FXAQ20P	FXAQ25P	FXAQ32P	FXAQ40P	FXAQ50P	FXAQ63P	
Cooling capacity	Nom.	kW	1.7	2.2	2.8	3.6	4.5	5.6	7.1	
Heating capacity	Nom.	kW	1.9	2.5	3.2	4.0	5.0	6.3	8.0	
Power input - 50Hz	Cooling	Nom.	0.017	0.019	0.028	0.030	0.020	0.033	0.050	
	Heating	Nom.	0.025	0.029	0.034	0.035	0.020	0.039	0.060	
Casing Colour	White (3.0Y8.5/0.5)									
Dimensions	Unit	HeightxWidthxDepth	mm 290x795x238				mm 290x1,050x238			
Weight	Unit	kg	11				14			
Fan-Air flow rate - 50Hz	Cooling	High/Low	m <sup>3</sup> /min	7.0/4.5	7.5/4.5	8/5	8.5/5.5	12/9	15/12	19/14
Sound power level	Cooling	Nom.	dBA	-						
Sound pressure level	Cooling	High/Low	dBA	34.0/29.0	35.0/29.0	36.0/29.0	37.5/29.0	39.0/34.0	42.0/36.0	47.0/39.0
Refrigerant	Type	R-410A								
Piping connections	Liquid/OD/Gas/OD/Drain	mm	6.35/12.7/VP13 (I.D. 13/O.D. 18)						9.52/15.9/VP13 (I.D. 13/O.D. 18)	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/220-240							
Current - 50Hz	Maximum fuse amps (MFA)	A	16							