



FXLQ20-25



BRC1E52A/B

BRC7C62

- › Stylish modern casing finished in pure white (RAL9010) and iron grey (RAL7011)
- › Unit can be installed as free standing model by use of optional back plate
- › Its low height enables the unit to fit perfectly beneath a window
- › Requires very little installation space
- › Wall mounted installation facilitates cleaning beneath the unit where dust tends to accumulate



- › Wired remote control can easily be integrated in the unit



INDOOR UNIT			FXLQ20P	FXLQ25P	FXLQ32P	FXLQ40P	FXLQ50P	FXLQ63P	
Cooling capacity	Nom.	kW	2.2	2.8	3.6	4.5	5.6	7.1	
Heating capacity	Nom.	kW	2.5	3.2	4.0	5.0	6.3	8.000	
Power input - 50Hz	Cooling	Nom.	0.049		0.090		0.110		
	Heating	Nom.	0.049		0.090		0.110		
Casing Colour	Fresh white (RAL9010) / Dark grey (RAL7011)								
Dimensions	Unit	HeightxWidthxDepth	600x1,000x232		600x1,140x232		600x1,420x232		
Weight	Unit	kg	27		32		38		
Fan-Air flow rate - 50Hz	Cooling	High/Low	7/6		8/6		11/8.5		
Sound power level	Cooling	Nom.	-		-		-		
Sound pressure level	Cooling	High/Low	35/32		38/33		39/34		
Refrigerant	Type	R-410A							
Piping connections	Liquid/OD/Gas/OD/Drain	mm	6.35/12.7/O.D. 21					9.52/15.9/O.D. 21	
Power supply	Phase/Frequency/Voltage	Hz/V	1~/50/60/220-240/220						
Current - 50Hz	Maximum fuse amps (MFA)	A	15						